

							
	AVENTOS HF top	AVENTOS HS top	AVENTOS HL top	AVENTOS HK top	AVENTOS HK-S	AVENTOS HK-XS	AVENTOS HKi
Lift mechanism	22F2500 22F2800	22S2200 22S2500 22S2800	22L2200 22L2500	22K2300 22K2500 22K2700 22K2900	20K2B00.N6 20K2C00.N6 20K2E00.N6	20K1101 20K1301 20K1501	24K2300 24K2500 24K2700 24K2800
Cover set	22.8000.NA (three colors)	22.8000.NA (three colors)	22.8000.NA (three colors)	22K80000.NA (three colors)	Included with the lift mechanism (three colors)		24K8000.NA (three colors)
Lever set	22F3200 22F3500 22F3900	22S3500	22L3200 22L3500 22L3800 22L3900	Included with the lift mechanism	Included with the lift mechanism	Included with the lift mechanism. Does require the use of CLIP top BLUMOTION or COMPACT BLUMOTION hinges	Included with the lift mechanism
Stabilizer rod			22Q1076U				
Connector set			22Q080Z				
Wood or wide aluminum hardware set	78Z5530T28 (frameless or partial overlay face frame) 78Z5530TA9 (large overlay face frame)	20S4200 or 20S4F01*	20S4200 or 20S4F01*	20S4200 or 20S4F01*	175H3100 or 175H3F00*	Cabinet mounting plates 20K5101, 20K51E1 or 20K5501 Door mounting plates 20K4101 or 20K4501*	24K42E1
Narrow aluminum hardware set	78Z550ATA6	20S4200A	20S4200A	20S4200A	20K4A00A02	20K4101A	24K4201A
Thin fronts		20S42T1	20S42T1	20S42T1			
Restriction clip	Integrated angle adjustment between 81° and full opening			Integrated angle adjustment between 75° and 107°	20K7A41 (100°) 20K7A11 (75°)	Use hinge angle restriction clip	Integrated angle adjustment between 75° and 107°
Template + drill bit	65.1051.02 + DB-5mm ZML.0040.02 65.5030.01 + DB-2.5mm	65.1051.02 + DB-5mm ZML.0040.02	65.1051.02 + DB-5mm ZML.0040.02	65.1051.02 + DB-5mm ZML.0040.02 ZML.2200	65.1051.02 + DB-5mm ZML.0040.02	65.1051.02 + DB-5mm ZML.0040.02	65.5840 M45.ZF19 M45.ZF04

*Mounting plate with bracket for use with large overlay five-piece doors



	AVENTOS HF top	AVENTOS HS top	AVENTOS HL top	AVENTOS HK top	AVENTOS HK-S	AVENTOS HK-XS	AVENTOS HKI
Maximum outside cabinet width	1828 mm (72")	1828 mm (72")	1828 mm (72")*	1828 mm (72")	1828 mm (72")	1828 mm (72")	1828 mm (72")
Maximum outside cabinet height	1219 mm (48")	800 mm (31-1/2")	580 mm (22-13/16")	610 mm (24")	610 mm (24")	610 mm (24")	610 mm (24")
Minimum outside cabinet height	480 mm (18-7/8")	350 mm (13-3/4")	300 mm (11-13/16")	205 mm (8")	186 mm (7-3/8")	238 (9-3/8")	162 mm (6-3/8")
Minimum outside cabinet depth	264 mm (10-3/8")	264 mm (10-3/8")	264 mm (10-3/8")	235 mm (10-7/16")	163 mm (6-7/16)	125 mm (4-15/16")	271 mm (10-11/16")
Lift mechanisms	2 options	3 options	2 options	4 options	3 options	3 options	4 options
Lever set	3 options	1 option	4 options	Included	Included	Included	Included
Hardware kits	3 options	4 options	4 options	4 options	3 options	3 options	2 options
Stabilizer rod	Not required	Not required	Yes	Not required	Not required	Not required	Not required
Restriction clips	Yes (104° or 83°)	Integrated (adjustable between 81° and full opening)	N/A	Integrated (adjustable from 75°-107°)	Yes (100° or 75°)	Yes (See hinge angle restrictions)	Integrated (adjustable from 75°-107°)
SERVO-DRIVE option	Yes	Yes	Yes	Yes	No	No	No
TIP-ON option	No	No	No	Yes	Yes	Yes	Yes

*If wider than 1228 mm (48-3/8") use of 22Q080Z (HL top) connector rod set is required

Blum templates		Blum drill bits	
Description	Part number	Description	Part number
Universal individual template	65.1051.02	5 mm right hand drill bit	DB-5mm
Universal template	ZML.0040.02		
PLATEMATE	65.5030.01	2.5 mm right hand drill bit	DB-2.5mm
Front marking template	ZML.2200		

— The information above is intended to be used as a guide only, please refer to AVENTOS brochures (LIT.AVT1001 and LIT.HKI1000) for exact specifications.